

030-7162-0

4

3


2

1

NOTES:

1. ALL DIMENSIONS ARE IN MM, GENERAL TOLERANCE IS 0.20MM;
2. ALL PINS LENGTH DON'T COUNT TIN ICICLES;
3. ELECTRICAL CHARACTERISTICS:
UNLESS OTHERWISE SPECIFIED, TESTING IS PERFORMED AT 25°C ±5°C
(FOR REFERENCE ONLY. USED FOR CUSTOMER INFORMATION)

ITEM	SPECIFICATION	TEST CONDITIONS	VALUE	UNIT
1	I _o : @ NO LOAD	INPUT 230 V, 50Hz	MAX 12.90	mA
2	P _{wo} : @ NO LOAD	INPUT 230 V, 50Hz	MAX 0.85	W
3	U _o : @ NO LOAD	INPUT 230 V, 50Hz	12.90±10%	V
4	I _e : @ CURRENT WITH LOAD	INPUT 230 V, 50Hz	MAX 17.75	mA
5	P _{we} : @ WATTAGE WITH LOAD	INPUT 230 V, 50Hz	MAX 3.55	W
6	U _a : @ NOMINAL LOAD	INPUT 230 V, 50Hz AT LOAD 166 mA	9.0	V
7	HI-POT: (1,5) TO (7,9)	/	4000VAC, 2 SEC	
8	RATED OUTPUT POWER	/	1.5	VA



SCHEMATIC

